

A surface mounted solution, suitable for internal or external locations.

UNRIVALLED SAFETY

Maintenance Safety Props
Easily activated for safe servicing

Designed with safety in mind, the lifts encompass a range of comprehensive safety features and are built in conformance with BS/EN standards and are CE Marked.



LED Traffic Lights
Interlocked to control panel



Sliding Personnel Gate
Safer alternative to 'drop down' designs



Material Gates
Fall protection gates with robust locking mechanisms



Hydraulic Lead-On Ramp Fixed, low gradient for easy access from ground level



Platform Safety Edge Enhancing safety for operators and minimising damage



ControlsLift can be operated from platform or ground level



Safety Curtain
Prevents access under platform
when lift is raised



Scan QR code to watch scissor lift video



CE-plated and built in conformity with EN1570 and the Machinery Directive, our scissor lifts are built for a lifetime of robust operation.

A FAST AND EFFICIENT WAY TO LOAD/UNLOAD TRAILERS

Robust and built for a lifetime of operation, our scissor lifts service the loading/unloading of vehicles with trailer bed heights of up to 1500mm.

Two different lift sizes are available; 6 and 9 cage variants which offer lifting capacities of up to 3000kg UDL (raise) and 5000kg UDL (lower). The compact footprint of the lifts also means that they can be located internally or externally and/or at sites which are restricted on space.

SPECIFICATION

6 and 9 roll cage models

Lifting capacities of up to 3000kg UDL (raise) and 5000kg UDL (lower)

Service range: 1500mm

Quick install – 1 day

No pits – surface mounted

Ideal for space restricted loading/unloading areas





SERVICING RAISED DOCKS

For lifting goods between split levels in the warehouse or at level access sites, our scissor lifts provide an ideal solution.

The lifts are delivered as plug-and-play, modular units that are fitted straight in less than 1 day – an instant solution for your loading and lifting requirements.

OUR SCISSOR LIFT RANGE

/6 Cage₄

External Dimensions	2050mm (w) x 3150mm (l) × 2215mm (h)
Platform Footprint	1820mm (w) x 2830mm (l)
Load Capacity	4 pallets/6 roll cages
Lifting Capacity	3000kg UDL raise and lower
Closed Height	180mm
Stroke	1500mm

/9 Cage⊿

External Dimensions	2952mm (w) × 5280mm (l) × 2215mm (h)
Platform Footprint	2650mm(w) x 3280mm (l)
Load Capacity	5 pallets/9 roll cages
Lifting Capacity	2500kg UDL raise, 5000kg UDL lower
Closed Height	180mm
Stroke	1500mm





Transdek UK Ltd

Bryans Close, Harworth, Doncaster, DN11 8RY. United Kingdom

t: +44 (0) 1302 752 276 e: info@transdek.com i: www.transdek.com













